

COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

		MO	DEL DAT	ΓA - F(OR CC	MPRE	SSED A	IR		
1	Manufacturer:	Chica	go Pneuma	ıtic						
	Model Number: CPVSd 34 26kW				Date:				08/16/23	
2	X Air-cooled Water-cooled							Type:		Screw
							# (of Stages:		1
3*	Full Load Opera	ıll Load Operating Pressure				150		psig b		
4	Drive Motor Nominal Rating				35		hp			
5	Drive Motor Nominal Efficiency				92.4		percent			
6	Fan Motor Nominal Rating (if applicable)				1.15		hp			
7	Fan Motor Nom	Motor Nominal Efficiency 32.7					percent			
	Input Power (kW)			Capa	city (acf	m) ^{a,d}	Specific Power (kW/100 acfm) ^d			
F	32.1					129			denn)	
8*	25.7				105				24.60	
	19.7				79				24.90	
Ī	14.0				54			25.70		
	8.5				29		29.10			
9*	Total Package Input Power at Zero Flow c, d				0.0		kW			
10	Isentropic Efficiency				66.3		%			
11	Specific Power (RW/100 ACFM)	35.00 30.00 25.00 20.00 15.00	, 20 Note: Graph Vote: Y-Axis Scal	is only a vi		ntation of th	100 te data in Secti		140	160

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
- a. Measured at the discharge terminal point of the compressor package in accordance with 15O 1217, Annex E, ACFM is actual cubic feet per minute at inlet conditions.

 b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.

 c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.

 d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

	olume Flow Rate	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power	
$\underline{m}^3 / \underline{min}$	ft ³ / min	%	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8		
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%	
1.5 to 15	53 to 529.7	+/- 5	+/- 6		
Above 15	Above 529.7	+/- 4	+/- 5		

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data